

Optic Distribution Frame

-Model: ODU



Key Features:

- 1) Standard size, light weight and reasonable structure
- 2) Splice tray inside changeable
- 3) Cable installation, wall mount & rack mount type
- 3) Can be used in 19", 23" standard distribution frame
- 4) Suitable for ribbon and single fiber
- 5) Various panel plate to fit different adapter interface
- 6) Front mark on the plate is easy for identification and operation
- 7) 24C, 48C, 72C,96C...etc optional, with or without fiber optic pigtails and adapters
- 8) Easy for management and operation

Application:

- 1) Telecommunications subscriber loop
- 2) Fiber to the home (FTTH)
- 3) LAN/WAN
- 4) CATV

Specification

Specification model	D(mm)	W(mm)	H(mm)
ODU12 cores	482	250	87
ODU24 cores	482	250	87
ODU 48 cores	482	250	132
ODU 72 cores	482	250	176
ODU 96 cores	482	250	228
ODU 144 cores	482	250	333

Technical Index

Environmental temperature	25 - 55°C
Atmosphere pressure	70~106Kpa
Insulating resistance	>2×10 ⁴ MΩ/500VDC
Relative humidity	<85%(when the temperature is below 30°C)
Voltage resistance strength	Under the effect of 15kv/DC/1min, non-puncture, and no arc-over

Product pic. in different position



